



DECLARATION OF PERFORMANCE

No: 200/P/2019



1. Unique identification code of the product type:

Steel and aluminium constructional components and sets — pergola SB400 480x285x324

2. Intended use or uses:

For external use, intended for buildings

3. Manufacturer:

**SELT Sp. z o. o.
45-449 Opole, ul. Wschodnia 23A**

4. The system or systems of assessment and verification of constancy of performance:

System 2+

5. Harmonised standard:

Harmonised standard EN 1090-1:2009+A1:2011

Certificate of Factory Production Control by Dekra Certification Sp. z o.o. no 2330-CPR-PL40/2

6. Declared performance:

Property	Level or classes	Harmonised technical specification
Performance class	EXC2 Steel: EN 1090-2:2008+A1:2011, Aluminium: EN 1999-1-1:2007+A1:2009	EN 1090-1:2009+A1:2011
Tolerance of dimensions and shape	Steel: functional tolerances - class 2 according to EN 1090-2:2008+A1:2011 Manufacturing-special tolerance: class m K according to EN 22768-1:1993 and EN 22768-2:1993 Aluminium: functional tolerances according to EN 1090-3:2008 Manufacturing-special tolerance: class m K according to EN 22768-1:1993 and EN 22768-2:1993	EN 1090-1:2009+A1:2011
Weldability	NPD – no applicable process	-
Fracture toughness	Steel: NPD – Austenitic steel - met to -400C acc EN1993-1-4:2006	-
Impact resistance	Aluminium: NPD – not required for aluminium products	-
Bearing capacity	PN-EN1999-1-1, see attached conceptual design and static calculations OT/BRI/021 + construction opinion 1/02/2019 (max. dimensions 4800x2850x3240 mm). Used National Annex for Poland	EN 1090-1:2009+A1:2011
Deformation in the serviceability limit state	PN-EN1993-1-1 i PN-EN1999-1-1 see attached conceptual design and static calculations OT/BRI/021+ construction opinion 1/02/2019 (max. dimensions 4800x2850x3240 mm). Used National Annex for Poland	
Fatigue strength	NPD	
Fire resistance	NPD - OT / BRI / 017 calculation (W4943 profile range)	
Reaction to fire	Material classification. Class A1	
Secretion of cadmium and its compounds	NPD	
Radioactivity	NPD	
Durability	Category of environment's corrosivity C2 according to PN-EN ISO 12944-2 Aluminium : Surface preparation PN-EN 1090-3 powder coating with thickness of the coating according to PN-EN ISO 2360 - 60 to 100 micrometers	
Execution	According to specification no. 620.000.000 and EN 1090-3 and EN 1090-2	

The performance of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (UE) no. 305/2011 on the sole responsibility of the producer referred to above:

Signed on behalf of the manufacturer:

Piotr Malorny, designer-constructor
Opole, 26.02.2019 r.



SELT Sp. z o.o.
ul. Wschodnia 23a, 45-449 Opole
tel. 77 55 32 100 fax 77 55 32 200
NIP 7543103311 REGON 363154414



2330

SELT Sp. z o. o.
45-449 Opole, ul. Wschodnia 23A

Year of marking
19

Dekra Certification Sp. z o.o. 2330-CPR-PL40/2

EN 1090-1+A1:2011

Description of the product: **Steel and aluminium constructional components and sets – pergola SB400**

Tolerance of dimensions and shape: **Steel: class 2 – EN1090-2:2008+A1:2011**

and for manufacturing: special: class m acc. EN 22768-1:1993 and class K acc. EN 22768-2:1993;

Aluminium: EN 1090-3:2008 and for manufacturing: special: class m acc. EN 22768-1:1993 and class K acc. EN 22768-2:1993;

Weldability: **NPD – no applicable process**

Fracture toughness: **Steel: NPD – austenitic steel - met to -400C acc EN1993-1-4:2006;**

Aluminium: not required for aluminium products

Reaction to fire: **Classified material. Class A1**

Secretion of cadmium: **NPD**

Radioactivity: **NPD**

Durability: **Category of environment's corrosivity C2 according to PN-EN ISO 12944-2**

Aluminium : Surface preparation PN-EN 1090-3; powder coating with thickness of coating according to PN-EN ISO 2360 - 60 to 100 micrometers

Construction characteristics:

Bearing capacity: PN-EN1999-1-1, see attached design assumptions and static calculations OT/BRI/021+construction opinion 1/02/2019 (max. dimensions 4800x2850x3240 mm).
Used National Annex for Poland

Deformation:PN-EN1993-1-1 and PN-EN1999-1-1, see attached design assumptions and static calculations OT/BRI/021+ construction opinion 1/02/2019 (max. dimensions 4800x2850x3240 mm).
Used National Annex for Poland

Fatigue strength: NPD

Fire resistance: NPD - calculations OT/BRI/017 (W4943 profile range)

Execution: in accordance with the specification of element no. 620.000.000 and EN 1090-2 and EN 1090-3, performance class: EXC2